



# SPR818

19" rack cabinet - 18 units - 600mm W x 800mm D

## Highlights:

---

- Stores up to 18 units of 19" Equipment
- Standard keylock for both doors
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front and rear in depth adjustable 19" profiles (max 740 mm)
- Tempered glass door with keylock
- Reversible door position



## Product information:

---

The SPR818 is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provides a solid and stable construction making it suitable for heavy equipment, storing up to 18 units inside. The SPR818 comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and leveling once correctly positioned. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19 " profiles provide great flexibility for installing equipment depending on its depth. Both front and rear doors are fitted with a standard keylock.

## Product Features:

---

|   |          |   |
|---|----------|---|
| Unit height                               |          | 18 HE   |
| Weight                                    |          | 136.69 lb   |
| Colours                                   |          | Black (RAL9004)   |
| Max. usable depth                         |          | 29.13 "   |
| Dimensions                                |          | 23.62 x 36.14 (38.90) x 31.50 " (W x H (incl. feet) x D)  |
| Accessories                               | Optional | KS600 - M6 x 16 mm bolt DIN7985 Black<br>KM600 - M6 Cage nuts   |
| Wheel                                     | Diameter | 1.97 "  |
| Accessories                               | Included | 4 x Key for sidepanel lock<br>1 x Allen key<br>4 x Levelling feet<br>4 x Key for front/back door<br>20 x KS600<br>20 x KM600              |
|   | Optional | SPR10CS - Rack interconnection slot<br>SPR80LR - L-Rail pair<br>SPR80FS - Fixed shelf<br>SPR80SS - Sliding shelf<br>SPR80PT - Rack plinth |
| Static load capacity (adjustable feet)    |          | 1763.70 lb  |
| Dynamic load capacity (transport castors) |          | 881.85 lb   |

## Variants:

---

- SPR818/B - Black version